

AFZ

PTO/SB/21 (08-03)

Approved for use through 08/30/2003. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

OFFICE TRANSMITTAL FORM JUL 18 2005 (to be used for all correspondence after initial filing)	Application Number	09/482,023	
	Filing Date	January 13, 2000	
	First Named Inventor	Devendra T. Barot	
	Art Unit	1764	
	Examiner Name	Basia Anna Ridley	
Total Number of Pages in This Submission	123	Attorney Docket Number	1927-00101

ENCLOSURES (Check all that apply)		
<input type="checkbox"/> Fee Transmittal Form	<input type="checkbox"/> Drawing(s)	<input type="checkbox"/> After Allowance communication to Technology Center (TC)
<input type="checkbox"/> Fee Attached	<input type="checkbox"/> Licensing-related Papers	<input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences
<input type="checkbox"/> Amendment/Reply	<input type="checkbox"/> Petition	<input checked="" type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)
<input type="checkbox"/> After Final	<input type="checkbox"/> Petition to Convert to a Provisional Application	<input type="checkbox"/> Proprietary Information
<input type="checkbox"/> Affidavits/declaration(s)	<input type="checkbox"/> Power of Attorney, Revocation Change of Correspondence Address	<input type="checkbox"/> Status Letter
<input type="checkbox"/> Extension of Time Request	<input type="checkbox"/> Terminal Disclaimer	<input checked="" type="checkbox"/> Other Enclosure(s) (please Identify below):
<input type="checkbox"/> Express Abandonment Request	<input type="checkbox"/> Request for Refund	Acknowledgment Post Card
<input type="checkbox"/> Information Disclosure Statement	<input type="checkbox"/> CD, Number of CD(s) _____	
<input type="checkbox"/> Certified Copy of Priority Document(s)	Remarks	
<input type="checkbox"/> Response to Missing Parts/Incomplete Application		
<input type="checkbox"/> Response to Missing Parts under 37 CFR 1.52 or 1.53		
SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT		
Firm or Individual name	Collin A. Rose, PTO Reg. No. 47,036 CONLEY ROSE, P.C.	
Signature	<i>Collin A. Rose</i>	
Date	July 14, 2005	

CERTIFICATE OF TRANSMISSION/MAILING			
I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below.			
Typed or printed name	Ella R. Sisco		
Signature	<i>Ella R. Sisco</i>	Date	July 14, 2005

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

126744/1927-00101

Best Available Copy

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Devendra T. Barot	§	Group Art Unit:	1764
		§		
Serial No.:	09/482,023	§		
		§		
Filed:	January 13, 2000	§	Examiner:	Basia Anna Ridley
		§		
For:	Combustion Chamber Design	§		
	For a Quench Gasifier	§	Confirmation No.:	6462



RESPONSE TO NOTIFICATION OF NON-COMPLIANT
APPEAL BRIEF DATED JUNE 28, 2005;
REPLACEMENT APPEAL BRIEF

Mail Stop Appeal Brief – Patents
Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

Att'y Docket No.: 1927-00101
Date: July 14, 2005

Sir:

This paper is filed in response to the Notification of Non-Compliant Appeal Brief dated June 28, 2005. The Examiner is requested to enter the appended Appeal Brief (provided in triplicate), which has been revised in accordance with the June 28 Notification of Non-Compliant Appeal Brief.

Applicant acknowledges receipt of an Advisory Action Before the Filing of an Appeal Brief of June 28, 2005, and appreciates that the Applicant's drawing changes were entered. Applicant also acknowledges receipt of an Advisory Action After the Filing of an Appeal Brief of June 28, 2005, and appreciates that the Applicant's reply filed April 6, 2005 (replacement Appeal Brief) was entered.

Appl. No. 09/482,023

Response dated July 14, 2005

Reply to Notification of Non-Compliant Appeal Brief of June 28, 2005

If any fees are inadvertently omitted or if any additional fees are required or have been overpaid, please appropriately charge or credit those fees to Conley Rose, P.C. Deposit Account Number 03-2769 (Atty. Docket No. 1927-00101).

Respectfully submitted,

A handwritten signature in cursive script, reading "Collin A. Rose", written in black ink on a white background.

Collin A. Rose

PTO Reg. No. 47,036

CONLEY ROSE, P.C.

P. O. Box 3267

Houston, TX 77253-3267

(713) 238-8000 (Phone)

(713) 238-8008 (Fax)

ATTORNEY FOR APPLICANT



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Devendra T. BAROT	§	Confirmation No.:	6462
		§		
Serial No.:	09/482,023	§		
		§		
Filed:	January 13, 2000	§	Group Art Unit:	1764
		§		
For:	Combustion Chamber	§		
	Design for a Quench	§		
	Gasifier	§	Examiner:	Basia Anna Ridley

APPEAL BRIEF

Mail Stop Appeal Brief – Patents

Date: July 14, 2005

Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

Sir:

Appellant hereby submits this Appeal Brief in connection with the above-identified application. A Notice of Appeal was filed on March 23, 2004.

I. REAL PARTY IN INTEREST

The real party in interest is Devendra T. Barot.

II. RELATED APPEALS AND INTERFERENCES

Appellant is unaware of any related appeals or interferences.

III. STATUS OF CLAIMS

Originally filed claims: 1-9.

Added claims: 10-40.

Withdrawn claims: 22-29.

Cancelled claims: 1-9, 11-14, 16, 21, 30, 33 and 36.

Presently rejected claims: 10, 15, 17-20, 31, 32, 34, 35 and 37-40.

Presently appealed claims: 10, 15, 17-20, 31, 32, 34, 35 and 37-40.

IV. STATUS OF AMENDMENTS

After the Examiner's last Office Action on the merits of December 23, 2003, Applicant filed an original Appeal Brief on May 27, 2004 pursuant to the March 23, 2004 Notice of Appeal. The Examiner found the original Appeal Brief to be not fully responsive and non-compliant. Applicant filed an Amendment (replacement Appeal Brief) on September 28, 2004, which was not entered due to defects in claim status and in the replacement Appeal Brief. Applicant filed an Amendment (second replacement Appeal Brief) on December 14, 2004, which was not entered due to changes in the appeal brief format rules. Applicant filed an Amendment on April 1, 2005 to make drawing changes, which was entered. Applicant filed an Amendment (third replacement Appeal Brief) on April 6, 2005, which was entered. The present Appeal Brief is submitted pursuant to a Notice of Non-Compliant Appeal Brief mailed subsequent to the April 6, 2005 Amendment.

V. SUMMARY OF CLAIMED SUBJECT MATTER

The various embodiments of the three independent claims (10, 34 and 37) are directed to a quench gasifier for gasifying hydrocarbon feedstocks such as residual oils, waste lubrication oils, petroleum cokes and coal. *Specification* (attached as Appendix B), p. 1, ll. 15-16. Appellant's drawing Figure 3 illustrates exemplary embodiments and is reproduced on the next page for convenience of discussion. All Figures are appended hereto as Appendix D.

With reference to Figure 3, first independent claim 10 defines a quench gasifier for gasifying ash-containing hydrocarbon feedstocks comprising: a combustion chamber (*Specification*, p. 1, ll. 20-24; p. 4, ll. 8-11; Fig. 3, "Combustion Chamber"); and a quench chamber adjacent to said combustion chamber (*Specification*, p. 1, l. 25 – p. 2, l. 7; Fig. 3, "Quench Chamber"), said combustion chamber including a throat adjacent to said quench chamber (*Specification*, p. 2, ll. 2-3, ll. 8-18; p. 4, ll. 9-15; Fig. 3, "Gasifier Throat"), characterized in that said throat includes: an inlet adjacent to said combustion chamber, said inlet having in inlet diameter (*Specification*, p. 5, ll. 9-14; Fig. 3, "D₁"); an outlet adjacent to said quench

chamber, said outlet having an outlet diameter (*Specification*, p. 5, ll. 9-14; Fig. 3, "D₄"); an inner surface and outer surface between said inlet and said outlet (*Specification*, p. 3, ll. 15-18; p. 5, ll. 1-7; Fig. 4, "Inner Shape" and "Outer Shape"); an electrical heating element between said inner and outer surfaces (*Specification*, p. 5, ll. 1-5; Figs. 3 and 4, "Heating Element"); and wherein said inlet diameter is greater than said outlet diameter (*Specification*, p. 5, ll. 9-14; Fig. 3, "D₁" and "D₄").




Figure 3

Similar to claim 10, claim 34 recites a quench gasifier comprising a combustion chamber and a quench chamber, wherein said combustion chamber includes a throat having an inlet, an outlet, an outer surface, an inner surface and a heating element between said two surfaces. Further, claim 34 recites an inner surface having a curved, conical contour (*Specification*, p. 3, ll. 10-12; p. 4, ll. 6-15; p. 5, ll. 9-14; Figs. 3 and 4).

Claim 37 recites identical structure to claim 10 except for the deletion of "wherein said inlet diameter is greater than said outlet diameter," and the addition of an electrical heating element "configured to maintain said inner surface at a temperature of at least 3000°F" (*Specification*, p. 2, ll. 21-22; p. 3, ll. 12-13; p. 5, ll. 1-7).

VI. GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL

The Examiner's first ground of rejection includes the assertion that pending claims 10, 15, 17-20, 34 and 37-40 are rendered obvious by Appellant's Admitted Prior Art (*Specification*, p. 1 and 2, Figures 1 and 2) in view of *Takada et al.* (JP 61-222939) (hereinafter called "*Takada*," patent and translation attached as Appendix C). The Examiner asserts that it would have been obvious to one having ordinary skill in the art to add the simple trough heating element of *Takada* to the more complex quench gasifier of Figures 1 and 2, and, more particularly, to add the heating element in the throat region of the gasifier.

The Examiner's second ground of rejection includes the assertion that pending claims 31, 32 and 35 are rendered obvious by Appellant's Admitted Prior Art in view of *Takada* and in further view of *Haneda et al.* (JP 61-235492) for similar reasons.

VII. ARGUMENT

A. First Ground of Rejection: Prior Art in view of *Takada*

Claims 10, 15, 17-20, 34 and 37-40 have been rejected according to the Examiner's first ground of rejection. Applicant feels the arguments below apply to all

of these claims. However, Applicant feels claims 37-40 are allowable for an additional reason, and will be addressed under a separate heading below.

1. Claims 10, 15, 17-20 and 34

Claims 10, 15, 17-20 and 34 are all limited by a heating element disposed between the inner and outer surfaces of the gasifier throat. The gasifier throat is part of a large and complex quench gasifier intended for dramatically heating and gasifying hydrocarbon feedstocks to produce, most importantly, synthesis gases (syngas) and, as a by-product, slag. The present specification teaches that a heating element may be placed in the throat of a quench gasifier to prevent plugging of the throat outlet area, to increase syngas production and carbon conversion without increasing oxygen and steam consumption, and to decrease the capital cost and improve reliability of the gasifier operations by eliminating the need for a soot recycle system and streamlining the heat-generating capabilities of the gasifier.

Takada discloses a trough for running slag generally horizontally, *i.e.*, for simply transporting slag and not for the complex treatment and processing of feedstocks, syngas and slag. The *Takada* trough stands alone and is open at the top, thereby exposing the trough's contents to ambient surroundings.

Takada is directed to the production of a high quality rock wool, and addresses the specific problem of displacement of the falling location of slag due to a slag coating that may occur at the "tip" of the trough. The displacement affects the quality of the final product. *Takada*, p. 2, 3rd para. Preventing the slag coating and, thereby, stabilizing the falling point of the slag ensures production of a high quality rock wool. *Takada*, p. 4, 1st para. *Takada* describes how the slag is created in "cupolas," or combustion gasifiers, and transported from the cupolas via a trough. *Takada*, p. 2, 1st para. *Takada* identifies the contact surface of the trough as a location where the slag coating may occur, and makes no reference to other locations where the slag coating, or slag solidification, is a problem.

Applicant submits that the Examiner has failed to make out a *prima facie* case of obviousness because a) there is no motivation to make the combination in the

Examiner's first ground of rejection, and b) there is no reasonable expectation of success for the proposed combination.

a) No Motivation to Combine

Appellant's Admitted Prior Art does not show a throat including an electrical heating element between the throat's inner and outer surfaces. Nor does Admitted Prior Art suggest heating a combustion gasifier throat. *Takada* does not show a combustion gasifier throat including an electrical heating element between the throat surfaces. Furthermore, *Takada* does not suggest the claimed element of a heating element disposed in a gasifier throat, or modification of the Admitted Prior Art gasifier to include the claimed element.

No "Express" Motivation

Neither Admitted Prior Art nor *Takada* include an express motivation to make the proposed combination. As alluded to above, an express motivation may include a suggestion to heat the throat in some way, for example, or some other suggestion of the desirability of the proposed combination. Admitted Prior Art does not make such a suggestion. *Takada* likewise lacks an express motivation because, despite recognizing the existence and purpose of a copula, or gasifier, *Takada* makes no mention of slag coatings in the copula, nor does it suggest heating a portion of the copula, including a throat. The sparse *Takada* disclosure does not contemplate gasifier design, throat or otherwise, and makes no suggestion of the applicability of the disclosure to any subject matter outside of a horizontal trough used to transport slag. In other words, it is not known from the *Takada* disclosure that slag solidification is a problem outside of a trough exposed to ambient surroundings and used to transport slag.

Lack of an express motivation to combine has been said to be suggestive of impermissible hindsight reasoning. See MPEP § 2145. Although an express motivation is not required, the Examiner's burden increases when such an express motivation cannot be found. In the absence of an express motivation to combine, the Examiner's sole thrust of her first ground of rejection is in the nature of the

problem to be solved, *i.e.*, slag solidification. To this issue, the Federal Circuit has held that when the required motivation to combine is found in the nature of the problem to be solved, this is simply a conclusory assertion lacking the clear and particular showing needed for a motivation to combine. The showing must be supported by actual evidence. See *Teleflex, Inc. v. Ficosa North America Corp.*, 299 F.3d 1313, 1334 (Fed. Cir. 2002). The Examiner's broad, conclusory assertion that the nature of the problem to be solved, *i.e.*, slag solidification, provides the requisite motivation to combine does not meet the Federal Circuit's clear and particular standard of the showing necessary to combine Admitted Prior Art with *Takada*. This requirement of evidencing a suggestion by the prior art to combine is rigorously enforced to avoid the dangers of impermissible hindsight.

As evidence that the Examiner has not made a clear and particular showing to make the proposed combination, the slag solidification problem of Admitted Prior Art and the slag solidification problem of *Takada* are incongruous. The slags contemplated by Admitted Prior Art contain vanadium trioxide (V_2O_3) or other metals or metal compounds that solidify at temperatures lower than 3000°F, thus requiring heating the throat of a gasifier combustion chamber to at least 3000°F for the purpose of preventing slag solidification. *Specification*, p. 2, ll. 14-16; p. 4, ll. 16-21. *Takada* does not contemplate a temperature high enough or environment suitable to prevent solidification of slags containing vanadium trioxide (V_2O_3) or other metals that solidify at temperatures lower than 3000°F. *Takada* teaches preventing slag solidification at 1472°F, less than half of the minimum preferred (3000°F) by the description in the specification. The slags considered by each reference are different, therefore the nature of the problem to be solved alone does not satisfy the Examiner's burden.

**The Proposed Modification Cannot Render the Prior Art
Unsatisfactory for Its Intended Purpose**

A motivation to combine prior art references also does not exist when the proposed modification renders the prior art unsatisfactory for its intended purpose.

See MPEP § 2143.01. *Takada* teaches pre-heating a trough to 1000°C (1832°F), then decreasing the temperature until the operation (running the slag) is performed at 800°C (1472°F). *Takada*, pp. 4-5. The intended purpose of operating the trough under these conditions is to provide a temperature high enough so that the slag will not solidify, thereby preventing generation of a slag coating and ensuring production of a high quality rock wool. *Takada*, pp. 2-5. Therefore, *Takada* describes the stand-alone environment of a trough, which is not suggested to be any part of a gasifier or other reactor, that provides an operating temperature of 1472°F.

The present specification describes heating the throat of a gasifier combustion chamber to at least 3000°F for several purposes: 1) preventing slag solidification, especially those slags containing vanadium trioxide (V_2O_3) or other metals or metal compounds that solidify at temperatures lower than 3000°F; 2) increasing gasifier carbon conversion; 3) increasing syngas production; 4) reducing steam consumption; 5) and increasing temperatures inside the gasifier without increasing oxygen consumption. *Specification*, p. 3, ll 1-8; p. 6, l. 11 to p. 7, l. 4. The high temperatures obtained by heating the throat will increase the carbon conversion of the gasifier by 0.1 to 3.0 percent, and decrease the steam requirement for the gasifier from approximately 0.25 to 0.35 pounds of steam per 1.0 pound of feedstock to approximately 0.15 to 0.25 pounds of steam per pound of feedstock.

Takada does not teach a temperature high enough or environment suitable to prevent solidification of slags containing vanadium trioxide (V_2O_3) or other metals that solidify at temperatures lower than 3000°F. *Takada* teaches an environment including a trough, which is not suggested to be any portion of a gasifier, and an operating temperature (1472°F) less than half of the minimum preferred (3000°F) by the description in the specification. Furthermore, the invention of *Takada* cannot achieve the other benefits mentioned above. Therefore, the teachings of *Takada* are insufficient to suggest the proposed modification to the prior art gasifier for its intended purpose. Under *In re Gordon*, 733 F.2d 900 (Fed. Cir. 1984), "if [the] proposed modification would render the prior art invention being modified

unsatisfactory for its intended purpose, then there is no suggestion or motivation to make the proposed modification.” MPEP § 2143.01.

b) No Reasonable Expectation of Success for the Proposed Modification

There is no reasonable expectation of success for making the modification because the *Takada* invention was intended for a trough open to ambient temperatures, while a gasifier is a much more harsh and dynamic environment. A reasonable expectation of success for making a modification is necessary in order to combine prior art references. MPEP § 2143.02; *In re Merck & Co., Inc.*, 800 F.2d 1091 (Fed. Cir. 1986). There is no suggestion in *Takada* that the materials used for the refractory (surface layer) or heating element, nor the construction of the trough as the trough is intended to be used, are satisfactory for the intended purposes of the present invention. Moreover, it is reasonable to assume that *Takada* discloses a heated trough including a heating element that is not satisfactory for use in a gasifier environment having temperatures two times as high as those described in *Takada*. Therefore, there is no reasonable expectation of success in modifying the prior art gasifier using the teachings of *Takada*.

2. Claims 37-40

Applicant submits that, with respect to claims 37-40, the Examiner has failed to make out a *prima facie* case for obviousness for the additional reason that the prior art does not teach all of the claimed limitations. Claim 37 recites a gasifier throat including “an electrical heating element between said inner and outer surfaces wherein said heating element is configured to maintain said inner surface at a temperature of at least 3000°F.” As previously stressed, none of the cited art (*Takada* and Admitted Prior Art) teaches maintaining a surface at a temperature of at least 3000°F, nor does the art teach a heating element configured to maintain said surface at said temperature. As also mentioned before, this high temperature, undisclosed by *Takada*, is critical to addressing those concerns presented by slags containing vanadium trioxide (V₂O₃) or other metals, as well as increasing the

production capabilities and efficiencies of the gasifier. Consequently, Applicant presented claims 37-40 to more narrowly claim a gasifier that is beyond the scope of anything taught by the cited art. As previously mentioned, *Takada* merely teaches heating slag up to a temperature less than half of 3000°F, and only teaches heating slags that do not contain vanadium trioxide and other such metal compounds.

For the reasons stated above, Applicant respectfully submits that the Examiner's first ground of rejection be withdrawn, and respectfully requests that claims 10, 15, 17-20, 34 and 37-40 be allowed.

B. Second Ground of Rejection: in Further View of *Haneda*

Claims 31, 32 and 35 were rejected based on the previously addressed first ground of rejection, and in further view of *Haneda*. Because Applicant believes Admitted Prior Art and *Takada* cannot be combined, Applicant also believes this combination in further view of *Haneda* must also be withdrawn regarding these claims, and the claims allowed.

VIII. CONCLUSION

For the reasons stated above, Applicant respectfully submits that the Examiner erred in rejecting all pending claims. If any fees or time extensions are inadvertently omitted or if any fees have been overpaid, please appropriately charge or credit those fees to Conley Rose, P.C. Deposit Account Number 03-2769 (Atty. Docket No. 1927-00101) and enter any time extension(s) necessary to prevent this case from being abandoned.

Respectfully submitted,



Collin A. Rose
PTO Reg. No. 47,036
CONLEY ROSE, P.C.
(713) 238-8000 (Phone)
(713) 238-8008 (Fax)
ATTORNEY FOR APPLICANT

APPENDIX A
CLAIMS APPENDIX

1 – 9. (Cancelled)

10. (Previously presented) A quench gasifier for gasifying ash-containing hydrocarbon feedstocks, comprising:

a combustion chamber for partially oxidizing carbon in the feedstocks to produce synthesis gases; and

a quench chamber adjacent to said combustion chamber, said combustion chamber including a throat adjacent to said quench chamber for directing said gases from said combustion chamber to said quench chamber, characterized in that said throat includes:

an inlet adjacent to said combustion chamber, said inlet having an inlet diameter;

an outlet adjacent to said quench chamber, said outlet having an outlet diameter;

an inner surface and outer surface between said inlet and said outlet;

an electrical heating element between said inner and outer surfaces; and

wherein said inlet diameter is greater than said outlet diameter.

11 - 14. (Cancelled)

15. (Previously Presented) The quench gasifier according to claim 10 wherein said inner surface comprises a wind tunnel profile.

16. (Cancelled)

17. (Previously Presented) The quench gasifier according to claim 10 wherein the ratio of said inlet diameter to said outlet diameter is at least 3.

18. (Previously Presented) The quench gasifier according to claim 17 wherein said ratio is in the range from 3 to 6.

19. (Previously Presented) The quench gasifier according to claim 10 wherein said quench chamber comprises a quench ring substantially axially adjacent to said throat outlet, such that the quench gasifier does not include a plenum chamber.

20. (Previously Presented) The quench gasifier according to claim 19 wherein said quench ring has an inner diameter that is greater than the diameter of said throat outlet.

21. (Cancelled)

22. (Withdrawn) A method for gasifying ash-containing hydrocarbon feedstocks comprising:

partially oxidizing the feedstock by mixing a feed stream, the feed stream comprising an oxidant, said feedstock, and a temperature moderator, in a combustion chamber comprising a reaction zone under conditions sufficient to produce synthesis gases with a predetermined carbon conversion rate, said conditions including a temperature of about 2000 – 3000°F; and

electrically heating a portion of the combustion chamber to a temperature elevated above 3000 °F.

23. (Withdrawn) The method of claim 22 wherein said oxidant is oxygen and wherein the synthesis gas production is increased without increasing the consumption of the oxygen.

24. (Withdrawn) The method of claim 22 wherein the synthesis gas production is increased without increasing the consumption of the feedstock.
25. (Withdrawn) The method of claim 22 wherein the temperature moderator is steam.
26. (Withdrawn) The method of claim 22 wherein the temperature moderator is carbon dioxide.
27. (Withdrawn) The method of claim 22 wherein the electrical heating comprises exposing said chamber portion to electromagnetic radiation.
28. (Withdrawn) The method of claim 22 wherein the electrical heating comprises applying electrical current to a resistor that is adjacent to said chamber portion.
29. (Withdrawn) The method of claim 22 wherein said portion includes substantially the entire hot face of the combustion chamber, such that the feed stream is preheated electrically, eliminating the use of a preheat burner.
30. (Cancelled)
31. (Previously Presented) The quench gasifier according to claim 10 wherein said heating element extends from said outlet to said inlet.
32. (Previously Presented) The quench gasifier according to claim 31 wherein said heating element is a spirally wound member having a first diameter near said throat inlet and a second diameter near said throat outlet, and wherein said first diameter is greater than said second diameter.

33. (Cancelled)

34. (Previously Presented) A quench gasifier for gasifying hydrocarbon feedstocks, comprising:

- a combustion chamber for partially oxidizing the carbon in the feedstocks to produce synthesis gases and slag;

- a quench chamber adjacent to said combustion chamber, said quench chamber having a gas outlet for directing said gases away from said quench chamber; and

- wherein said combustion chamber includes a throat for directing said gases and said slag from said combustion chamber to said quench chamber, said throat comprising:

- an inlet;

- an outlet;

- an outer surface between said inlet and said outlet;

- an inner surface between said inlet and said outlet;

- a heating element between said inner and outer surfaces; and

- wherein said inner surface has a curved, conical contour.

35. (Previously Presented) The quench gasifier according to claim 34 wherein said heating element is near said inner surface such that said heating element substantially follows said curved, conical contour of said inner surface.

36. (Cancelled)

37. (Previously Presented) A quench gasifier for gasifying ash-containing hydrocarbon feedstocks, comprising:

- a combustion chamber for partially oxidizing carbon in the feedstocks to produce synthesis gases; and

a quench chamber adjacent to said combustion chamber, said combustion chamber including a throat adjacent to said quench chamber for directing said gases from said combustion chamber to said quench chamber, characterized in that said throat includes:

an inlet adjacent to said combustion chamber, said inlet having an inlet diameter;

an outlet adjacent to said quench chamber, said outlet having an outlet diameter;

an inner surface and outer surface between said inlet and said outlet; and

an electrical heating element between said inner and outer surfaces wherein said heating element is configured to maintain said inner surface at a temperature of at least 3000°F.

38. (Previously Presented) The quench gasifier according to claim 37 wherein the feedstocks include metal compounds such as vanadium trioxide, and wherein the feedstocks are substantially free of solidified metal compounds.

39. (Previously Presented) The quench gasifier according to claim 37 wherein said heated inner surface causes the partially oxidized carbon in the feedstocks to increase in the range of 0.1 to 3.0 percent.

40. (Previously Presented) The quench gasifier according to claim 37 wherein said heated inner surface causes a steam consumption rate in the range of 0.15 to 0.25 pounds of steam per pound of feedstocks.

Clean Copy of Post-Amendment Specification

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

5 The present application claims the benefit of U.S. Provisional Application Serial No. 60/162,959, filed November 2, 1999, entitled Combustion Chamber Design for a Quench Gasifier, which is hereby incorporated herein by reference.

**STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR
DEVELOPMENT**

10 Not applicable.

REFERENCE TO A MICROFICHE APPENDIX

Not applicable.

BACKGROUND OF THE INVENTION

15 Quench gasifiers are used to gasify ash containing hydrocarbon feedstocks such as residual oils, waste lubrication oils, petroleum cokes and coal. A typical quench gasifier design is shown in Figure 1 (Reference: U.S. Patent No. 4,828,579). The feedstock, the oxidant and a temperature moderator (either steam or carbon dioxide) are injected into the top portion of the gasifier through a burner and are mixed with one another in the reaction zone below the burner. Steam and carbon
20 dioxide (CO₂) moderate the temperatures in the reaction zone and also act as reactants. The partial oxidation reactions that take place in this portion of the gasifier, called the combustion chamber, maintain the combustion chamber temperatures in the 2000 to 3000 °F range. The combustion chamber is lined with refractory materials such as alumina. Approximately 90.0 to 99.5 percent of the carbon in the feedstock is converted to the synthesis gases (syngas).

25 The bottom portion of the quench gasifier, called the quench chamber, is separated from the combustion chamber by the floor of the combustion chamber as shown in Figure 1. The

combustion chamber has an internal longitudinal length L_1 , an external longitudinal length L_2 , and an internal diameter D_1 . A portion of the floor of the combustion chamber forms a constricted gasifier throat having an internal diameter D_2 . The quench chamber is partially filled with water and is not lined with refractory. The quench chamber consists of three main components: the quench ring, the dip tube and the draft tube as shown in Figure 1. The main functions of the quench chamber are to cool down the synthesis gases generated in the combustion chamber by mixing them with water and to saturate the gases with water vapor.

The constricted gasifier throat area which directs the gases from the combustion chamber to the quench chamber is normally the coolest portion of the combustion chamber because of its distance from the gasifier burner and the burner flame. This area tends to be cooler than the rest of the combustion chamber also due to its proximity to the quench ring through which cooling water is injected into the quench chamber. As a result, the ash in the feedstock, which is in its molten or semi-molten form in the center portion of the combustion chamber, tends to solidify and form deposits or plugs in the throat area of the gasifier. These deposits are more likely to form with feedstocks that contain metal compounds such as vanadium trioxide (V_2O_3) because these compounds solidify at temperatures lower than 3000 °F. In addition to causing shutdown of the gasifier, these compounds also react and damage the alumina type refractories that have been used in existing gasifiers (see U.S. Patent No. 5,464,592).

A new gasifier throat design is proposed in this invention to avoid ash deposits and plugging in the throat area of the gasifier and to avoid damage to the refractories in the throat area. The proposed design will use electrical resistor heating to achieve temperatures in the range of 3000 to 3500 °F. The new design will also use refractory materials like silicon carbide and silicon nitride that can withstand higher temperatures and larger temperature shocks than alumina. With

this new design, it will be possible to increase the gasifier carbon conversion, reduce the steam (moderator) consumption and reduce the frequent damages that have been experienced to the refractories in the throat area of existing gasifiers. The proposed design will also decrease the capital cost of oil gasification plants by eliminating the need for soot recycle system downstream and will reduce the plant operating cost by improving the reliability of the gasifier operations.

BRIEF SUMMARY OF THE INVENTION

Electrical heating and new refractory materials are proposed for the gasifier throat area, which will increase the throat area operating temperatures without increasing oxygen consumption. The high temperatures will improve the gasification process by increasing carbon conversion, reducing steam or CO₂ consumption and by eliminating ash deposits and plugging. The preferred shape for the gasifier throat with electrical heating is the wind tunnel shape proposed in the previous U.S. Patent No. 4,574,002. The gasifier throat area is heated electrically using graphite resistors to maintain temperatures in the throat area between 3000 and 3500 °F. At these temperatures, higher carbon conversion is achieved and ash deposits are melted and pushed out of the throat area by high syngas velocities achieved in the constricted throat area. The throat area refractories consist of three layers. The innermost layer or hot face that is exposed to the hot gases consists of silicon carbide or silicon nitride or a combination of the two materials. The middle layer consists of graphite resistors and the outermost layer consists of insulating refractories.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1: Prior Art Example 1, Typical Quench Gasifier Design with Conical or Funnel Shape Throat.

Figure 2: Prior Art Example 2, Typical Quench Gasifier Design with Wind Tunnel Shape Throat.

Figure 3: New Art Example, New Quench Gasifier Design with Electric Heating of the Throat Area.

Figure 4: Details of the New Throat Design.

Figure 5: New Combination Quench Gasifier.

5 **DETAILED DESCRIPTION OF THE INVENTION**

A previous patent (U.S. Patent Number 4,574,002) suggests changing the shape of the gasifier throat to avoid ash deposits and plugs in this area. The wind tunnel shape proposed in U.S. Patent No. 4,574,002 is shown in Figure 2. The combustion chamber again has an external longitudinal length L_2 and an internal diameter D_1 . However, the modified gasifier throat causes
10 the internal longitudinal length L_3 to decrease compared to the length L_1 of Figure 1. Additionally, the modified gasifier throat has an internal diameter D_3 . This shape provides a better chance of avoiding deposits and plugs in the throat area than the shape shown in Figure 1. However, the wind tunnel shape is also susceptible to deposits and plugs particularly when feedstock contains metals or metal compounds that solidify at temperatures lower than 3000 °F due to the distance of
15 the throat from the burner and its proximity to the quench ring component of the gasifier.

In order to avoid ash deposits and plugs in the throat area, particularly with feedstocks that contain vanadium trioxide type metal compounds, it is necessary to maintain temperatures in the throat area in the 3000 to 3500 °F. At these higher temperatures, vanadium oxide type compounds (vanadium trioxide and all other metal compounds that melt and flow easily at temperatures in the
20 3000 to 3500 °F range) will melt and easily flow out of the throat and into the quench chamber. The throat refractory will have to withstand these high temperatures. Alumina type refractories that have been used in the throat area in the past are frequently damaged by vanadium oxide type compounds (see U.S. Patent No. 5,464,592).

This patent application proposes electrical heating (either with resistors or with electromagnetic waves) of the throat area to avoid low temperatures in the throat area. This patent application also proposes that the hot face of the throat area refractory be silicon carbide, silicon nitride or a combination of the two. As shown in Figure 4, the electrical heating elements will be made of graphite and graphite heating elements will be used behind the hot face material. The outermost layer of the throat block will be made of insulating refractory. This insulating refractory will prevent high temperature exposure of the combustion chamber floor and the quench ring.

This new design will make it possible to control temperatures in any desired range in the throat area up to an upper temperature limit of about 3500 °F. The design proposed in Figure 3 shows an approximate wind tunnel shape, and a combustion chamber having an internal diameter D_1 and a modified gasifier throat having an internal diameter D_4 . The throat does not have to be exactly in the wind tunnel shape. The essential features of this design are that the ratio D_1/D_4 be in the range of 3 to 6 and that the diameter of the throat shape should decrease as you move away from D_1 portion of the throat.

Figure 3 only shows an application for the electrical heating concept in the throat area of a vertical quench gasifier. In fact, this concept can also be applied to a horizontal reactor as shown in Figure 5 or to the entire hot face of the combustion chamber. This concept can also be applied to any extension of the gasifier exit area such as the transition block area of Figure 5.

Figure 5 shows a combination quench gasifier. A portion of the syngas generated in the combustion chamber is quenched in water and the remaining syngas is quenched (cooled down) by injecting a cold quench gas.

The new combustion chamber throat design, shown in Figure 3 and Figure 4, will be more successful in preventing plugging in the throat area. This design will also eliminate the frequent

damages that have occurred to the throat refractory, because silicon carbide and silicon nitride can withstand higher temperatures and the erosive and corrosive effects of vanadium oxide type compounds better than alumina.

5 This patent suggestion also proposes eliminating the plenum chamber area shown in Figure 2. The quench ring area of the traditional quench gasifier is prone to frequent damage (References: U.S. Patent No. 4,828,580 and Patent No. 4,828,579). This new design (shown in Figure 3) will be more successful in preventing damage to the quench ring than the designs shown in Figures 1 and 2, because the distance between the throat opening and the quench ring is longer in the new design. Overall, this new design will improve the gasifier on-stream time (reliability of
10 operations) and thereby lower the gasifier operating cost.

The high temperatures obtained by electrical heating in the throat will also increase the gasification reaction rates and thereby increase the carbon conversion of the gasifier by 0.1 to 3.0 percent. This in turn will increase the syngas production of the gasifier without increasing either oxygen consumption or feedstock consumption.

15 The use of electrical heating and silicon carbide type refractories in the throat area will also reduce the consumption of the steam as a temperature moderator, because it will not be necessary to moderate the temperatures. Normally approximately 0.25 to 0.35 pound of steam is required for gasification of every 1.0 pound of residual oil or coke or coal. With this new design, the steam requirement will drop to 0.15 to 0.25 pound of steam per pound of feedstock.

20 Due to the increased carbon conversion achieved with this design, it will be possible to eliminate the soot recovery and soot recycle system that is normally employed downstream of the gasifier. Thus electrical heating of the throat area will reduce the gasification plant capital cost. The concept of electrical heating of the refractory can be extended to the entire gasifier hot face. If

Serial No.: 09/482,023
Filed: January 13, 2000

the entire hot face of the gasifier (not just the throat area) is electrically heated, it will be possible to preheat and cure the gasifier refractories electrically. There will be no need for using a preheat burner, a flue gas cooler and an aspirator (steam ejector) for preheating refractories. This will reduce the gasification plant capital cost further.

PAT-NO: JP361222939A
DOCUMENT-IDENTIFIER: ~~JP361222939A~~
TITLE: HEATING TROUGH
PUBN-DATE: October 3, 1986

INVENTOR-INFORMATION:

NAME	COUNTRY
TAKADA, MASAYUKI	
TAKAGI, RYOJI	
BESSHO, NOBORU	

ASSIGNEE-INFORMATION:

NAME	COUNTRY
NIPPON STEEL CHEM CON/A LTD	

APPL-NO: JP60061803
APPL-DATE: March 28, 1985

INT-CL (IPC): C03B037/085

US-CL-CURRENT: 65/346

ABSTRACT:

PURPOSE: The base material which forms the outer structure of the trough is provided, on its inner surface, with an insulating layer, a specific heat-generating layer and a protecting layer, so that the slag is prevented from solidifying in the inner surface of the trough and rock wool of high quality is obtained without coating.

CONSTITUTION: The base 1 of a heat-resistant material such as iron is lined with a fire-proofing material such as ceramic fibers in its inner surface to form an insulating layer 2, the layer 2 is provided on its inner surface, with a heat-generating layer 3 which is prepared by embedding electric heaters 5 in a refractory material such as high alumina castable refractory, further, a protecting layer 4, which contacts with the slag is formed with a heat-resistant, corrosion-resistant material such as carbon plates on the heat-generating layer 3. As a refractory for the insulating layer 2, are cited silica fiber, alumina fiber carbon fiber in addition to ceramic fiber and silicon carbide or high alumina is used as a heat-resistant, corrosion-resistant material for the protecting layer 4.

COPYRIGHT: (C)1986, JPO&Japio

⑫ 公開特許公報(A)

昭61-222939

⑤ Int.Cl.⁴
C 03 B 37/085

識別記号

庁内整理番号
8216-4G

④ 公開 昭和61年(1986)10月3日

審査請求 未請求 発明の数 1 (全3頁)

⑭ 発明の名称 加熱トラフ

⑮ 特 願 昭60-61803

⑯ 出 願 昭60(1985)3月28日

⑰ 発 明 者	高 田	征 幸	東京都世田谷区野沢 2-29-15
⑰ 発 明 者	高 木	良 二	泉佐野市上町 1丁目 8番13号203
⑰ 発 明 者	別 所	昇	泉佐野市上町 1丁目 8番13号203
⑰ 出 願 人	新日鐵化学株式会社		東京都中央区銀座 5丁目 13番16号
⑰ 代 理 人	弁理士 小松 秀岳		外 1 名

明 細 書

1. 発明の名称

加熱トラフ

2. 特許請求の範囲

トラフの外形を形成する基材内面に断熱層を設け、その内面に発熱体を埋設した耐火物からなる発熱層を形成し、その内面に溶解材料流と接する保護層を設けてなる加熱トラフ。

3. 発明の詳細な説明

産業上の利用分野

この発明は鉱物繊維、例えばロックウールの原料を溶解した溶解材料流(いわゆるノロ)を流すための樋(トラフ)に関する。

従来の技術

ロックウール等の鉱物繊維の製造にあたり、高炉スラグ又は玄武岩、輝緑岩等の天然岩石を電気炉で溶解するか、或いは原料をコークスと混ぜて衝風式溶解炉(キューボラ)で溶解し、その溶解材料(ノロ)を出出口から樋(トラフ)により製綿装置に誘導し、製綿装

置でロックウールを製造することが従来から実施されている。

ところで、上記トラフは第2図に示すような断面がし字形で内部が空洞の鉄皮からなる基材1が外形を形成し、この内部空洞が冷水の循環路6になっているものである。

このような構造のトラフでは、トラフ内面との接触面に凝固物による被覆(いわゆるノロコーティング)が多量に形成され、それを排除するときにロックウール製品内にノロ塊が混入することになり、更に、トラフ先端にコーティングが発生すると製綿装置内のノロ落下位置が変動する。この落下位置の変動は製品の品質に大きな影響があり、操業上ならびに製品の品質維持から重大な問題になっていた。

発明が解決しようとする問題点

この発明は、上記ノロコーティングが発生しないような構造のトラフを提供しようとするものである。

問題点を解決するための手段

上記問題を解決するためのこの発明のトラフの構成は、トラフの外形を形成する基材内面に断熱層を設け、その内面に発熱体を埋設した耐火物からなる発熱層を形成し、その内面に溶解材料流（ノロ）と接する保護層を設けてなる加熱トラフである。

図面を参照して具体的に説明すると、第1図はこの発明のトラフの横断面図であって、耐熱性材料例えば鉄製の基材 1の内面に耐火性断熱材例えばセラミックファイバーを張りつけた断熱層 2を形成し、その内面に耐火物例えば高アルミナ系キャスト耐火物中に、例えばカンタル線（Mo-Si系発熱体）製の電熱体 5を埋設した発熱層 3を設け、その上面、すなわち最も内面にノロと接する表面層 4を耐熱・耐食性材料例えばカーボンプレートで形成したものである。

上記断熱層 2の耐火性断熱材としてはセラミックファイバーの外にシリカファイバー、

らなる断熱層 2、アルミナ系キャスト耐火物にカンタル線からなる電熱体 5を埋設した発熱層 3、最内部に表面層 4としてカーボンプレートを張ったトラフにおいて、このカーボンプレートの表面温度、ヒーター（電熱体）の温度および鉄皮温度を測定したとき、それぞれの関係は下記の表に示すとおりであった。

表（温度の単位は℃）

表面温度	ヒーター温度	鉄皮温度
355	500	155
520	700	230
800	1000	320

また、このトラフで実際にノロを誘導する実験では、キューボラからの出湯 2時間前からヒーターを1000℃にして加熱しておき、出湯後、流出するノロの温度が次第に上昇するに従ってヒーターへの入力を下げ、最終的に800℃で運転をした。その結果14時間の間ノロコーティングの掃除は一度もする必要がな

アルミナファイバー、カーボンファイバー等が用いられ、表面層 4の耐熱・耐食性材としてはカーボンプレートの外にシリコンカーバイド、ハイアルミナ等が用いられる。

作 用

上記構造を有するこの発明のトラフによれば、電熱体 5に電流を通すことによって、それから発生する熱で、ノロと接する表面層 4を高温に保つことができる。したがって、ノロがトラフ内面で凝固することがないのでコーティングが発生しない。その結果、ノロ塊が製綿装置内に流入することがなく、かつ、トラフの先端部にコーティングが生成しないので製綿装置におけるノロの落下点が安定し、高品質のロックウールを製造することができる。

以下実施例によって、この発明のトラフの性能を具体的に説明する。

実施例

鉄製基材 1内面にセラミックファイバーが

かった。

発明の効果

以上説明したように、この発明のトラフによればノロコーティングの発生が防止でき、したがって、高品質の綿物繊維を安定して製造することができる。

4. 図面の簡単な説明


第1図は、この発明のトラフの一例の横断面図、

第2図は、従来のトラフの横断面図である。


1…基材、2…断熱層、3…発熱層、
4…表面層、5…電熱体。

特許出願人 新日鐵化学株式会社
代理人 弁理士 小 松 秀 岳
代理人 弁理士 旭 宏

第 1 図



第 2 図



PTO: 2003-511

Japanese Published Unexamined (Kokai) Patent Application No. S61-222939, published October 3, 1986; Application No. S60-61803, filed March 28, 1985; Int. Cl.⁴: C93B 37/085; Inventor(s): Masayuki Takada et al.; Assignee: Nippon Steel Chemical Corporation; Japanese Title: Kanetsu Torafu (Heating Trough)

Specification

1. Title of Invention

Heating Trough

2. Claim

A heating trough, characterized by providing the following layers: a heat insulating layer in the inner surface of a substrate that forms the outer shape of the trough; a heat generating layer made of a fire retardant material with a heat generating element embedded in the inner surface of the heat insulating layer; a protective layer in the inner surface of the heat generating layer, which is in contact with a fused material stream.

3. Detailed Description of the Invention

[Field of Industrial Application]

This invention pertains to troughs for running a fused material stream (so-called slag) wherein the raw materials of mineral fibers such as rock wool are fused.

[Prior Art]

As for a conventional production of the mineral fibers, blast furnace slag or natural

rocks such as basalt and diabase are fused by using electric furnaces or the raw materials are mixed with coke, and the mixtures are fused in air blast fusion furnaces (cupolas). The slag is introduced into drafts making devices from tap holes via troughs so as to produce rock wool.

The troughs are designed in Fig.2 as follow. A substrate 1 whose cross-section is an L shape and whose interior is made of a hollow shell forms the outer shape. This inner hollow functions as a circulating circuit 6 for cooling water.

As for the trough with this structure, a large amount of a coating (so-called a slag coating) due to a coagulated substance is formed to the contact surface with the inner surface of the trough. When the slag coating is cleaned up, a slag lump is mixed into a rock wool product. If a coating occurs to the tip of the trough, a falling location of the slag inside the drafts making device displaces. The displacement of the falling location gives a significant effect on the quality of the product. This effect is critical with respect to the operation and the maintenance of the product quality.

[Problem of Prior Art to Be Addressed]

The present invention is produced to offer a trough with a structure to prevent a generation of the slag coating.

[Measures to Solve the Problem]

In order to eliminate the aforementioned disadvantage, the invention is as a heating trough, characterized by providing the following layers: a heat insulating layer in the inner

surface of a substrate that forms the outer shape of the trough; a heat generating layer made of a fire retardant material with a heat generating element embedded in the inner surface of the heat insulating layer; a protective layer in the inner surface of the heat generating layer, which is in contact with slag.

As the invention is described in detail with reference to the drawings, Fig.1 is a horizontal cross-sectional view illustrating a trough. A heat insulating layer 2 with a fire retardant heat insulating material such as a ceramic fiber lined in the inner surface of heat insulating iron substrate 1 is formed. A heat generating layer 3 with a kanthal wire (a Mo-Si heat generating element) heating element 5 embedded in the inner surface of heat insulating layer 2, such as a high alumina castable fire retardant material, is provided. A surface layer 4 that is brought into contact with slag is formed onto the upper surface of heat generating layer 3, more specifically the inner most surface, by using a heat and corrosion resistant material such as a carbon plate.

Other than the ceramic fiber, a silica fiber, an alumina fiber and a carbon fiber are used as fire retardant heat insulating materials for heat insulating layer 2. Other than the carbon plate, silicon carbide and high alumina are used as heat and corrosion resistant materials for surface layer 4.

[Effect]

According to the trough of the invention that has the aforementioned structure, by running current to heating element 5, surface layer 4 that is in contact with slag is maintained at a high temperature using a heat generated from heating element 5. Accordingly, the slag will

not solidify in the inner surface of the trough. No coating occurs. As a result, a slag lump will not flow into the drafts making device, and no coating occurs to the tip of the trough. The falling point of the slag in the drafts making device is stabilized. Subsequently, high quality rock wool can be produced.

Using the embodiment, the performance of the trough by the invention is described hereinbelow in detail.

[Embodiment]

Using a trough that comprises the following layers: ceramic fiber heat insulating layer 3 in the inner surface of iron substrate 1; heat generating layer 3 with kanthal wire heating element 5 embedded in an alumina castable fire retardant material; a carbon plate lined on the most inner section as surface layer 4, the surface temperature of the carbon plate, the temperature of the heater (heating element) and the shell temperature are measured, the table as shown below indicates a relationship among these temperatures.

Table (°C as the temperature unit)

Surface temperature	Heater temperature	Shell temperature
(Please refer to the original descriptions)		
365	580	155
520	700	230
800	1000	320

At a testing that actually induces slag by the trough, the heater is heated to 1000°C in

advance 2 hours before slag is ejected from a cupola. After the ejection of the slag, an input to the eater is reduced as the temperature of the ejected slag gradually increases. The operation is finally performed at 800°C. As a result, no cleaning is required for 14 hours to remove a slag coating.

[Advantageous Result of the Invention]

As described above, according to the trough of the invention, the generation of a slag coating is prevented. Thus, a high quality mineral fiber is stably produced.

4. Brief Description of the Invention

Fig.1 is a horizontal cross-sectional view illustrating an example of a trough of the invention. Fig.2 is a horizontal cross-sectional view illustrating prior art trough.

1...Substrate

2...Heat insulating layer


3...Heat generating layer

4...Surface layer


5...Heater

Translations Branch
U.S. Patent and Trademark Office
11/13/02
Chisato Morohashi

第 1 図



第 2 図






Figure 1 (Prior Art)




Figure 2 (Prior Art)




Figure 3




Figure 4




Figure 5

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.